



**#416SE**

**MODEL 4/15**

**CAR LENGTH QUAD RAILS  
WITH FRONT EXTENSION**

MTU015

- **Made in USA** with Ultimate Precision and Strength
- Fits Model 4/15 Carbines with Rails Extending Beyond Front Sight
- Aircraft Aluminum Extrusion with Integral Spinal Cords for Alignment
- Picatinny Rails with 19 Top Slots, 23 Bottom Slots, 25 Left/Right Slots
- Simple Installation, No Gunsmith or Tool Required
- Solid Locking Feature for Secure Fit and Zero Retention
- 18 UTG Rubber Rail Guards Included



MTU015

**#416SE**

**MODEL 4/15**


**CAR LENGTH QUAD RAILS  
WITH FRONT EXTENSION**

**Made in USA**

# MODEL 4/15 CARBINE QUAD RAILS WITH FRONT EXTENSION INSTALLATION GUIDE

MTU015

**Caution: Make sure firearm is not loaded.  
Remove magazine and examine chamber.  
Use safe handling procedures at all times.**



1. Separate the pre-assembled mount and arrange all parts on a flat surface.



2. Use a handguard removal tool to pull down Delta Ring and remove the handguards.



3. Install the Top Cover onto the barrel by aligning the inner two spinal cords against the central groove area on the barrel nut, and push for a tight fit. Make sure the Front Sight goes into the rectangular cut of the Top Cover.



4. Press downward the Top Cover to pull back Delta Ring, and then release toward the barrel to allow the Front Cap to fit snugly inside the transversal channel in the middle of the Top Cover. Make sure that the Top Cover is evenly situated.



5. Repeat step 4 for the Bottom Cover installation.



6. Tighten all the four screws with the provided Allen wrench to lock the top/bottom covers rock solidly.



7. Place the Bottom Extension under the front end of the Top Cover. Make sure that the bayonet lug sits in the groove inside the Bottom Extension.



8. Tighten the four screws with the provided Allen wrench to lock the Bottom Extension with the Top Cover.



9. Your mount is ready for you to install scope and other accessories. Rubber rail guards can also be installed for comfort and protection.